


Data transmission cable - BiTLAN F/UTPs cat. 5e outdoor 200 MHz



Application:

F/UTP cat. 5e outdoor cables are applicable to computer networks with operating frequency band up to 200 MHz. Suitable for transmission of data, audio and video signals, with bitrate up to 1 Gb/s. Collective polyester/aluminum foil with CuSn drain wire protect against external electromagnetic interferences. Dedicated for fixed installations within outdoor structured cabling systems as per PN-EN 50173-1, PN-EN 50288-2-1, ISO/IEC 11801 2nd ed., IEC 61156-5, ANSI/TIA/EIA 568-C.2 standards, as well as within industrial networks exposed to external electromagnetic interferences.

Cable suitable for outdoor overhead installations thanks to application of integrated steel messenger wire (self-supported cable) and PE outer jacket, resistant to UV radiation.

Technical data:

Operating temperature:

Fixed installation: -30°C to +80°C

Flexible connections: -10°C to +50°C

Bending radius: 10 x Ø

DC loop resistance at 20 °C (max): 190 Ω/km

Insulation resistance (min): 5 GΩ x km

Resistance unbalance: ≤ 2%

Capacitance at 1 kHz: 50 ± 5 nF/km

Capacitance unbalance at 1kHz (max): 1600 pF/km

Nominal voltage: 150V

Test voltage:

AC 50 Hz: 700V

DC: 1000V

Characteristic impedance: 100 ± 5Ω

NVP value: 67%

Return loss (min):

f = 4÷10 MHz: 20 + 5lg(f)

f = 10÷20 MHz: 25

f = 20÷200 MHz: 25 - 7lg(f/20)

Screen attenuation within the range of 30 ÷ 200 Mhz (min.): 50 dB

Transfer impedance at 10 Mhz (max): 100 mΩ/m

Construction:

Conductors: solid round copper conductors

Insulation: special polyolefin compound

Core identification: wh/bu-bu, wh/or-or, wh/gn-gn, wh/bn-bn

Core arrangement: cores twisted in pairs, pairs twisted together

Screen: polyester/aluminum foil with tinned copper drain wire Ø 0,4 mm

Self-support: integrated steel messenger wire Ø 1,0 mm



Outer sheath: PE compound, UV resistant

Outer sheath colour: black RAL 9005

Construction:

ID	Construction	Cu wire	O.D. [mm]	Copper weight	Cable weight	Band [Mhz]
	F/UTP cat.5e	24AWG (0,50)	6,5 (6,5x10,7)	17	50	200

Performance test charts and data:



Freq.	Min. RL (dB)		Max. IL (dB)		Min. NEXT (dB)		Min. PS NEXT (dB)		Min. ACR-F (dB)	
Mhz	Standard	BITNER ¹⁾	Standard	BITNER ¹⁾	Standard	BITNER ¹⁾	Standard	BITNER ¹⁾	Standard	BITNER ¹⁾
1	20,0		2,0	2,0	65,3	85,4	62,3	77,4	63,8	86,2
4	23,0	29,4	4,1	3,7	56,3	78,5	53,3	70,5	51,8	77,5
8	24,5	30,4	5,8	5,2	51,8	69,3	48,8	62,4	45,7	69,8
10	25,0	33,4	6,5	5,8	50,3	71,0	47,3	65,1	43,8	66,7
16	25,0	34,5	8,2	7,3	47,2	66,9	44,2	56,4	39,7	62,4
20	25,0	32,9	9,3	8,2	45,8	64,7	42,8	56,6	37,8	60,5
25	24,3	34,1	10,4	9,2	44,3	63,4	41,3	56,2	35,8	58,1
31,25	23,6	35,4	11,7	10,3	42,9	60,7	39,9	51,4	33,9	56,3
62,50	21,5	37,0	17,0	14,7	38,4	58,4	35,4	48,2	27,9	51,3
100	20,1	36,2	22,0	18,6	35,3	55,1	32,3	46,0	23,8	49,0

¹⁾ Typical average test result