
Product: Industrial Grade Switch

1-port 10/100/1000Mbps + 1-port 1000Mbps SFP Fiber

Model: IS-1SF60001



RoHS

Overview

Industrial PoE switch, 1 Port 10/100/1000Mbps and 1 port 1000Mbps SFP, for connecting with devices like computer, switch, hub, server, etc, as well as powering network camera, industrial VoIP phone, wireless AP and other PoE supported devices. Specially designed for harsh outdoor applications. Its 6KV network port surge protection can adapt to harsh outdoor environment and ensure the reliability of the uninterrupted PoE system. Power input also chooses industry-standard types of power

Features

- 1 Port 10/100/1000Mbps Ethernet , 1 port 1000Mbps SFP
- Automatic MAC address learning and aging
- Automatically support IGMP (Multicasting)
- 10/100/1000Mbps Auto-negotiation , auto-MDI-MDI-X
- LED indicators for monitoring power/link/activity
- Supports 10/100/1000Mbps-Full/Half-duplex
- Supports DIN-Rail and Wall mounting installation
- Supports Daisy-Chain connection
- Supports Broadcast Storm Control
- Supports Relay output for power failure
- Supports QoS and ensuring the transmission of VoIP packets;
- Super lightning protection, IP40 protection.
- Excellent heat elimination without cooling fan.
- Redundant dual DC power inputs.
- Apply to Urban Intelligent Traffic Monitoring System (ITS), Safe City.
- Harsh industrial environment or higher requirement
- 6KV port Lightning protection
- -40°C~+85°C operating temperature range.



Technical Specification

Product Name	1 Port 10/100/1000M Industrial Switch
Product Model	IS-1SF60001
Interface	1x 10/100/1000Base-T port + 1x 1000Mbps SFP slot
Network Protocols	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u; 100Base-TX/FX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3x; IEEE802.3af, IEEE802.3at
Network Media	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-TX: Cat6 or later UTP(≤100 meter)
Fiber Media	Multi-mode: 2KM Single-mode: 20/40/60/80KM
Performance Specification	Bandwidth: 10Gbps Packet Buffer Memory: 1M Packet Forwarding Rate: 1488000pps/port MAC Address Table: 8K
Forwarding Mode	Store-and-Forward
Protection	6KV Lightning protection, IP40 protection
LED Indicators	Power: PWR; Link; PoE; Link/Act
Power Supply	Input Voltage: DC48~57V (PoE) /Terminal block DC12~48V (Converter) /Terminal block



Other Specifications	
Working Environment	Working temperature: -40~+85°C ; Storage temperature: -40~+85°C Relative Humidity: 5%~95 %(no condensation)
Industry Standard	FCC CFR47 Part 15,EN55022/CISPR22, Class A EMS: IEC61000-4-2 (ESD): $\pm 8\text{kV}$ (contact), $\pm 15\text{kV}$ (air) IEC61000-4-3 (RS): 10V/m (80MHz-2GHz) IEC61000-4-4 (EFT): Power Port: $\pm 4\text{kV}$; Data Port: $\pm 2\text{kV}$ IEC61000-4-5 (Surge): Power Port: $\pm 2\text{kV/DM}$, $\pm 4\text{kV/CM}$; Data Port: $\pm 2\text{kV}$ IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz) IEC61000-4-16 (Common mode conduction): 30V (cont.), 300V (1s)
Shell	IP40 protect grade, metal shell
Installation	DIN-Rail or Wall mounting
Packing List	1×Industrial PoE Switch (plus terminal block) 1× User Manual/Certificate of quality/Warranty card 1× DIN-Rail mounting kit
Certification	CE mark, commercial; FCC Part 15 Class B; VCCI Class B EN 55022 (CISPR 22), Class B
MTBF	300,000 hours
Weight & Size	Product Weight: 0.36 KG Packing weight: 0.46KG Product size (L×W×H): 12.5cm× 10.4cm× 3.4cm Packing size(L×W×H): 17cm× 13.5 cm× 5.5cm
Warranty	5-years