

A

B

C


D

A

B

C

D



KROME 45°-110 DUAL IDC



Specifications : SCALE 1/4

Material :


1. Panel : SPCC, 1.5 mm thickness with Black(RAL 9005) color painted.
2. RJ45 Jack :
 - 2-1. Housing : ABS, UL 94V-0.
 - 2-2. Contact Bracket : PC, UL 94V-2, Transparent color.
3. RJ45 Jack Contact :
 - 3-1. Material : Phosphor Bronze with Nickel plated.
 - 3-2. Contact area : 50 micro-inch Gold plated Plug contact area.
4. IDC :
 - 4-1. Housing : PC+Glass Fiber, UL 94V-2.
 - 4-2. Terminal : Phosphor Bronze with Tin plated.
5. Jack Bracket Set : ABS, UL 94V-0.
6. Support Bar : SPCC, 1.5 mm thickness with Black(RAL 9005) color painted.
7. PCB : FR4, UL 94V-0.

Performance :


- a. T568A & T568B wiring.
- b. Insertion force : 20N max. (IEC 60603-7-4)
- c. Retention strength : 7.7 kg between Jack and Plug.
- d. Operating temperature : -10°C to 60°C. (ISO/IEC 11801, ANSI/TIA/EIA 568 B.2)
- e. Life(mating cycles) :
 - *Jack : 750 cycles min. (ISO/IEC 11801, IEC 60603-7-4)
 - *IDC : Suitable for 22-26 AWG stranded and solid wire, compatible with both 110 & Krone punch down tools.
- f. The Cat.5e transmission performance is in compliance with the ANSI/TIA/EIA 568 B.2 standard.



CAT.5E 6 PORT PCB MODULE



SCALE 1/1

GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.005 X.XX ±0.05 X.X ±0.1	DRAWING	02.JUN.2010	MARK	 EXCELLENCE WIRE IND CO LTD	
	CHECK	02.JUN.2010	JANE		
	APPROVAL	02.JUN.2010	JAIMY		
	DATE		NAME	ITEM NO.: 3J01-C01-00013	
SCALE		1/4 (A4)	UNIT	mm	DES.: CAT.5E UNSHIELDED PATCH PANEL
		DRAWING NO.		AAAEB4802133101 PA48T-KDA-CEC(SA3)	
		DRAWING CLASSIFICATION		S	SHEET 1 OF 1
				A3	

10cm