
VALUE S/FTP (PiMF) Patch Cord, Cat.6 (Class E), green, 0.5 m

Product No. 21.99.1323


Manufacturer

Manufacturer No.

EAN (single piece)













Patch cable for networking connections between devices. Prepared double shielded Twisted Pair cable with screened RI-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. Plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded wire. Complete braid shielding. Pairs shielded with aluminium clad polyester foil.

For a structured cabling system we recommend to use the following components: ROLINE Cat.6 S/FTP Cable, Solid Wire, AWG23: 21.15.0890 (100 m), 21.15.0891 (300 m); VALUE Cat.6 Flush/Surface Mount Wall Jack, shielded, white: 25.99.8492/25.99.8392; VALUE Cat.6 19" Patch Panel, 24 Ports, shielded: 26.99.0353 (black), 26.99.0354 (grey); VALUE Cat.6 S/FTP Patch Cord, grey, 5 m: 21.99.0805. Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class E specifications.

Technical specifications		
Manufacturer	VALUE	
Product group	Twisted Pair Cable	
Product type	S / FTP patch cable PiMF	
Colour	green	

Length	0.5 m
Shield type	PiMF
Transfer quality	Cat6 / Class E
Impedance	100 Ohm
Quantity of wires	8
Conductor type	Wire
Crossed	No
Colour (Spout)	green
Cable LSOH	No
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Weight	21.6 g
Height of packaging (single piece)	10 mm
Width of packaging (single piece)	85 mm
Depth of packaging (single piece)	85 mm
Package weight (single piece)	0.032 kg