



EasySplicer

EasySplicer is a professional fusion splicer for fibre optic installations. Easy to use, excellent splicing and yet very affordable.

- For both Singlemode and Multimode fibres.
- Splicing time of less then 7 seconds.
- Loss estimation.
- Pull test of performed splices.
- Built in oven.
- Easy to use and to carry along.
- Perfect for the FTTH installer.

The EasySplicer is a Swedish made Fusion Splicer, designed for working daily with fiber optic installations.

It's small and handy to bring along to any kind of work. The construction is made very rugged and even if splicing should take place under good conditions (indoors) it is still designed to be used out in the field.



The design of the EasySplicer differs a bit from other Fusion Splicers as it is made with focus on the installer/user. Many of the Splicers on the market are, even if very competent, difficult to use and require a lot education before they can be operated.

The EasySplicer is very easy to learn how to use. It doesn't take more than an hour for anyone to learn how to use the Splicer and start working with it. The EasySplicer operates with three buttons only and mostly the user only have to use the main button to perform the splicing.

Still, the precision of the unit is extremely high. It makes typical splicing with a loss of 0, 03 dB (Singlemode). After splicing it pull tests the splice and makes a loss estimation of the splice were it also tells if something is wrong. Such information is also provided before splicing (like; Bad fiber and Dirty fiber).







The following components are included:

- Splicer
- Cleaver
- Miller stripper
- Carrying bag
- Fiber holders 250 and 900µm
- Electrodes
- Power supply 230 VAC/6 VDC
- Accupack 2200 mAh

The battery-pack inside the unit is small but very powerful. The unit can perform some 40 splices (with oven operation) before it needs to be recharged. Extra battery-packs can also be sold separately (and easily be exchanged in the unit by the installer).

The EasySplicer is constantly calibrating itself for environment changes (like; moisture). This can also be done manually, for ex. When starting the work of the day. Calibration is very easily performed (within seconds) and makes sure that the splicing is made perfect.

The EasySplicer is using the V-grove method for splicing (same as Ribbon-splicers are using) which has made it possible to keep the size small of the unit. It also makes this unit extremely cost-effective.

The SBFS1 is one of the most inexpensive splicers on the market, yet with a performance of 4-5 times more expensive units.

The EasySplicer is truly a grand innovation for making Fiber optic Networks. It will revolutionary the ease to build such networks and it will cut the costs for the customers which will generate more work for the installers!





Technical specifications:

- Splicing method V-grove (cladding alignment).
- Fiber Types SMF, MMF 50/125µm and 62.5/125µm fiber, 250µm primary and 900µm secondary coated fiber.
- Fiber Handling Fiber holders, 2 pairs (250 and 900)
- ✓ Splice Programs 2 pre-defined. SMF & MMF
 ✓ Typical Splice Loss 0.03dB SMF, 0.01dB MN
- ✓ Typical Splice Loss 0.03dB SMF, 0.01dB MMF
 ✓ Typical Cycle Time 70 ± 500 / m Typical Cycle Time 7s + 50s (splice cycle + oven cycle)
- Sleeve Dimensions Max 64mm length, 2-5mm diameter supported by oven
- Communication USB, mini usb plug.
- Memory Internal 1MB, External SD-Card.
- Monitor LCD, color, 2.8, 320x240 pixels
- Magnification Camera 140x
- Operating Environment 0-40°C, max 95% RH, non-condensing
- Size 230x98x53mm
- Weight 800a
- Power Sources External power supply, 6V, 1.25A, 100-240VAC 50-60Hz,
- ✓ Built in Li-Ion battery pack: Splicing Capacity 40 splicing cycles with over.
 ✓ Additional Features Loss estimation, Fiber fault detection, Pull test,SD-card for logging etc.





Contactdetails:

seba service nv Industriepark Mechelen Zuid Egide Walschaertsstraat 22G B - 2800 Mechelen

Tel: 02 272 05 90 (B) 010 307 04 25 (NL) E-mail: klantenservice@easysplicer.be

EasySplicer is produced by the Swedish Company SB Scandinavia.